

EARTHMAX SR 45 PLUS - Fiche de données



Description

EARTHMAX SR 45 PLUS est un pneu radial All Steel (Tout Acier) spécialement conçu pour les tombereaux rigides et il est idéal pour les opérations sur de longs parcours. Le dessin de la bande de roulement de EARTHMAX SR 45 PLUS réduit au minimum les bruits et vibrations.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Tombereau rigide

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
27.00 R 49	CUT RESISTANT COMPOUND	E4	**	223 B	19.50/4.0	--	746	2702	1214	8095	TL	440
27.00 R 49	HEAT RESISTANT COMPOUND	E4	**	223 B	19.50/4.0	--	746	2702	1214	8095	TL	654
27.00 R 49	STANDARD COMPOUND	E4	**	223 B	19.50/4.0	--	746	2702	1214	8095	TL	540
33.00 R 51	CUT RESISTANT COMPOUND	E4	**	235 B	24.00/5.0		910	3065	1369	9313	TL	605
33.00 R 51	HEAT RESISTANT COMPOUND	E4	**	235 B	24.00/5.0		910	3065	1369	9313	TL	815
33.00 R 51	STANDARD COMPOUND	E4	**	235 B	24.00/5.0		910	3065	1369	9313	TL	705

Printed on 19/04/2024 19:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..