

EARTHMAX SR 45 PLUS - Fiche de données



Description

EARTHMAX SR 45 PLUS est un pneu radial All Steel (Tout Acier) spécialement conçu pour les tombereaux rigides et il est idéal pour les opérations sur de longs parcours. Le dessin de la bande de roulement de EARTHMAX SR 45 PLUS réduit au minimum les bruits et vibrations.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Tombereau rigide

| SIZE | Version | USACode | TRA Code | Star R | LI/SS | RIM REC | RIM ALT | OW | OD | SLR | RC | Type | TMPH |
|------------|-------------------------|----------|----------|--------|-------|-----------|---------|------|-------|------|-------|------|------|
| 27.00 R 49 | CUT RESISTANT COMPOUND | 94045655 | E4 | ** | 223 B | 19.50/4.0 | -- | 29.4 | 106.4 | 47.8 | 318.7 | TL | 301 |
| 27.00 R 49 | HEAT RESISTANT COMPOUND | 94049813 | E4 | ** | 223 B | 19.50/4.0 | -- | 29.4 | 106.4 | 47.8 | 318.7 | TL | 448 |
| 27.00 R 49 | STANDARD COMPOUND | 94049806 | E4 | ** | 223 B | 19.50/4.0 | -- | 29.4 | 106.4 | 47.8 | 318.7 | TL | 370 |
| 33.00 R 51 | CUT RESISTANT COMPOUND | 94073306 | E4 | ** | 235 B | 24.00/5.0 | | 35.8 | 120.7 | 53.9 | 366.7 | TL | 414 |
| 33.00 R 51 | HEAT RESISTANT COMPOUND | 94073320 | E4 | ** | 235 B | 24.00/5.0 | | 35.8 | 120.7 | 53.9 | 366.7 | TL | 558 |
| 33.00 R 51 | STANDARD COMPOUND | 94073313 | E4 | ** | 235 B | 24.00/5.0 | | 35.8 | 120.7 | 53.9 | 366.7 | TL | 483 |

Printed on 19/04/2024 23:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..