

## EARTHMAX SR 454 - Spécifications techniques



### Description

L'EARTHMAX SR 454 est un pneu radial tout en acier spécialement conçu pour les camions de transport rigides. La conception unique de la bande de roulement E-3 et la rainure centrale spéciale permettent d'améliorer les tractions latérales et la maniabilité sur les surfaces molles et boueuses. Ce pneu est spécialement conçu pour les vitesses plus élevées, les longs trajets et une température de service plus froide. La construction tout acier avec des ceintures en acier multicouches offre une protection optimale contre les chocs et l'infiltration de roches, afin d'améliorer le temps de disponibilité pour une productivité plus élevée. L'épaule droite de l'EARTHMAX SR 454 maximise le contact avec le sol pour une maniabilité et une stabilité optimales, sans oublier la réduction des vibrations et du bruit.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Tombereau rigide

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	40.00 R 57
LI/SS	250 B

## Dimensions US Standard

Usa code	94075553
TMPH	823
Overall Width (inch)	43.9
Overall Diameter (inch)	138.2
Static Loaded Radius (inch)	62.3
Rolling Circumference (inch)	419.4
Rim Rec	29.00/6.0
Rim Alt	32.00/6.0
Star Rating	**
TRA Code	E3

## Load capacity (lbs)

mph / psi	80	83	87	91	94	98	102
30	110000	113500	117000	120000	123500	128000	132500

Printed on 25/04/2024 18:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..