

## EARTHMAX SR 45 - Spécifications techniques



### Description

EARTHMAX SR 45 est un pneu radial **All Steel** (Tout Acier) particulièrement conçu pour les tombereaux rigides. EARTHMAX SR 45 est le pneu idéal pour toutes les opérations qui exigent une capacité de traction élevée.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Tombereau rigide

Version	STANDARD COMPOUND
Type	TL
Tyre Size	18.00 R 33
LI/SS	195 B

## Dimensions International Standard

TKPH	220
Overall Width (mm)	505
Overall Diameter (mm)	1870
Static Loaded Radius (mm)	856
Rolling Circumference (mm)	5608
Rim Rec	13.00/2.5
Star Rating	***
TRA Code	E4

## Load capacity (Kg)

km/h / bar	7.25	7.50	7.75	8.00
50	11200	11500	11800	12150

Printed on 23/04/2024 17:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..