



# EARTHMAX SR 47 TP - Spécifications techniques

## Description

L'EARTHMAX SR 47 TP (E-4) est un pneu radial tout en acier spécialement conçu pour les camions de transport rigides opérant dans des conditions nécessitant une traction et une résistance à la crevaison maximales. La profondeur de la bande de roulement E-4 garantit une grande résistance à l'usure, même sur de longues distances, ce qui réduit les temps d'arrêt et augmente la productivité. EARTHMAX SR 47 TP est idéal pour toutes les tâches exigeant à la fois de la traction et de la stabilité, en particulier sur les terrains boueux ou glissants. Disponible en version standard et composés résistants aux coupures.

## UM

US Standard

## Construction

 RADIAL

## Machinery

OTR: Tombereau rigide

Version	STANDARD COMPOUND
Type	TL
Tyre Size	24.00 R 35
LI/SS	209 B

## Dimensions US Standard

Usa code	94074211
TMPH	301
Overall Width (inch)	25.6
Overall Diameter (inch)	86
Static Loaded Radius (inch)	38.8
Rolling Circumference (inch)	260.8
Rim Rec	17.00/3.5
Rim Alt	--
Star Rating	**
TRA Code	E4

## Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	30900	32000	34200	35300	36400	37500	38600	39700	40800

Printed on 03/05/2024 15:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..