

EARTHMAX SR 475 - Spécifications techniques



Description

EARTHMAX SR 475 est un pneu radial All Steel particulièrement conçu pour les tombereaux rigides. Il est idéal pour les milieux durs et rocheux et les transports de longue distance. Le dessin unique de la bande de roulement génère moins de chaleur dans un climat chaud. La carcasse robuste All Steel et les ceintures d'acier offrent une grande stabilité et résistance aux coupures et crevaisons. EARTHMAX SR 475 a été développé avec un épaulement en forme de carré pour garantir un niveau de manœuvrabilité élevé, en optimisant le contact sur le sol.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Tombereau rigide

Version	STANDARD COMPOUND
Type	TL
Tyre Size	18.00 R 33
LI/SS	195 B

Dimensions International Standard

TKPH	292
Overall Width (mm)	490
Overall Diameter (mm)	1860
Static Loaded Radius (mm)	860
Rolling Circumference (mm)	5721
Rim Rec	13.00/2.5
Star Rating	***
TRA Code	E4

Load capacity (Kg)

km/h / bar	7.25	7.50	7.75	8.00
50	11200	11500	11800	12150

Printed on 03/12/2023 15:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..