

EARTHMAX SR 47 - Fiche de données



Description

EARTHMAX SR 47 (E-4) est un pneu radial **All Steel** (Tout Acier) particulièrement conçu pour les tombereaux rigides qui opèrent dans des conditions nécessitant la plus grande résistance aux coupures et perforations dans les milieux rocheux. Le dessin unique de la bande de roulement d'une profondeur E-4 réduit l'usure en assurant une vie plus longue du pneu même sur de longs parcours. Ceci se traduit par des temps d'arrêt machine réduits, ce qui augmente la productivité. Disponible avec mélange standard ou résistant aux coupures.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Tombereau rigide

| SIZE | Version | USACode | TRA Code | Star R | LI/SS | RIM REC | RIM ALT | OW | OD | SLR | RC | Type | TMPH |
|------------|-------------------------|----------|----------|--------|-------|-----------|-----------|------|------|------|-------|------|------|
| 18.00 R 33 | CUT RESISTANT COMPOUND | 94064489 | E4 | *** | 195 B | 13.00/2.5 | | 20.1 | 74.2 | 34.1 | 223.4 | TL | 115 |
| 18.00 R 33 | CUT RESISTANT COMPOUND | 94045815 | E4 | ** | 191 B | 13.00/2.5 | -- | 20.1 | 74.2 | 34.1 | 223.4 | TL | 115 |
| 18.00 R 33 | HEAT RESISTANT | 94070190 | E4 | ** | 191 B | 13.00/2.5 | -- | 20.1 | 74.2 | 34.1 | 223.4 | TL | 156 |
| 18.00 R 33 | STANDARD COMPOUND | 94064472 | E4 | *** | 195 B | 13.00/2.5 | | 20.1 | 74.2 | 34.1 | 223.4 | TL | 140 |
| 18.00 R 33 | STANDARD COMPOUND | 94046102 | E4 | ** | 191 B | 13.00/2.5 | -- | 20.1 | 74.2 | 34.1 | 223.4 | TL | 140 |
| 21.00 R 33 | CUT RESISTANT COMPOUND | 94057801 | E4 | ** | 200 B | 15.00/3.0 | -- | 22.6 | 78.8 | 36.1 | 240.7 | TL | 155 |
| 21.00 R 33 | STANDARD COMPOUND | 94057788 | E4 | ** | 200 B | 15.00/3.0 | -- | 22.6 | 78.8 | 36.1 | 240.7 | TL | 185 |
| 21.00 R 35 | CUT RESISTANT COMPOUND | 94064380 | E4 | ** | 201 B | 15.00/3.0 | 17.00/3.0 | 23 | 80.5 | 37.2 | 248.5 | TL | 179 |
| 21.00 R 35 | HEAT RESISTANT COMPOUND | 94069842 | E4 | ** | 201 B | 15.00/3.0 | 17.00/3.0 | 23 | 80.5 | 37.2 | 248.5 | TL | 243 |
| 21.00 R 35 | STANDARD COMPOUND | 94065288 | E4 | ** | 201 B | 15.00/3.0 | 17.00/3.0 | 23 | 80.5 | 37.2 | 248.5 | TL | 209 |
| 24.00 R 35 | CUT RESISTANT COMPOUND | 94041244 | E4 | ** | 209 B | 17.00/3.5 | -- | 26.4 | 85.9 | 38.7 | 258.5 | TL | 182 |
| 24.00 R 35 | CUT RESISTANT COMPOUND | 94060917 | E4 | *** | 212 B | 17.00/3.5 | -- | 26.4 | 85.9 | 38.7 | 258.5 | TL | 182 |
| 24.00 R 35 | STANDARD COMPOUND | 94041251 | E4 | ** | 209 B | 17.00/3.5 | -- | 26.4 | 85.9 | 38.7 | 258.5 | TL | 216 |
| 24.00 R 35 | STANDARD COMPOUND | 94060924 | E4 | *** | 212 B | 17.00/3.5 | -- | 26.4 | 85.9 | 38.7 | 258.5 | TL | 216 |

Printed on 27/02/2024 20:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..