

EARTHMAX SR 48 - Spécifications techniques



Description

EARTHMAX SR 48 est un pneu radial All Steel (Tout Acier) particulièrement conçu pour les tombereaux rigides. Ce pneu assure une meilleure traction et une extraordinaire résistance à l'usure - même pour les opérations les plus exigeantes dans des milieux rocheux. Le pneu est idéal pour le transport de charges lourdes. L'épaule en forme de carré protège le flanc contre les coupures et des dommages. EARTHMAX SR 48 présente une carcasse robuste All Steel qui confère une résistance exceptionnelle aux chocs et crevaisons par les pierres en optimisant la productivité.

UM

US Standard

Construction



RADIAL

Machinery

OTR: Tombereau rigide

Version	STANDARD COMPOUND
Type	TL
Tyre Size	24.00 R 35
LI/SS	209 B

Dimensions US Standard

Usa code	94059713
TMPH	258
Overall Width (inch)	26.2
Overall Diameter (inch)	85.8
Static Loaded Radius (inch)	39.1
Rolling Circumference (inch)	260.7
Rim Rec	17.00/3.5
Star Rating	**
TRA Code	E4
Tread Depth	73

Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	30900	32000	34200	35300	36400	37500	38600	39700	40800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11/05/2025 22:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..