

## EARTHMAX SR 49 - Spécifications techniques



### Description

EARTHMAX SR 49 (L-4) est un pneu radial All Steel (Tout Acier) conçu pour les chargeurs et bulldozers, les tombereaux surbaissés (LPDT) et les chargeurs-transporteurs (LHD). EARTHMAX SR 49 garantit des performances exceptionnelles pour les opérations difficiles dans les mines, pour lesquelles traction et stabilité excellentes représentent des conditions essentielles. Le dessin non directionnel et le mélange spécial résistant aux coupures du pneu assurent une durabilité extraordinaire.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Bulldozer • Chargeur-transporteur LHD • Chargeur • Tombereau surbaissé

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	35/65 R 33

## Dimensions US Standard

Usa code	94057108
Overall Width (inch)	35.4
Overall Diameter (inch)	81.1
Static Loaded Radius (inch)	35
Rolling Circumference (inch)	241.1
Rim Rec	28.00/3.5
Rim Alt	--
Star Rating	****/***
TRA Code	E4/L4

## Load capacity (lbs)

mph / psi

\* In case of underground mine application, consult your servicing dealer or BKT representative.

Printed on 13/04/2024 20:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..