

EARTHMAX SR 50 - Spécifications techniques



Description

EARTHMAX SR 50 (L-5) est un pneu radial **All Steel** (Tout Acier) particulièrement conçu pour les chargeuses. La carcasse résistante et les bourelets de protection sont idéaux pour les opérations les plus exigeantes. EARTHMAX SR 50 est réalisé dans un mélange spécial résistant aux coupures qui réduit l'usure et assure donc une vie plus longue du pneu. Les opérateurs apprécieront aussi l'excellente traction associée à une grande stabilité et à une conduite confortable.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Chargeur

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	26.5 R 25
LI/SS	202 A2

Dimensions International Standard

Overall Width (mm)	690
Overall Diameter (mm)	1772
Static Loaded Radius (mm)	806
Rolling Circumference (mm)	5334
Rim Rec	22.00/3.0
Star Rating	*
TRA Code	L5

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00
10	12850	13200	14000	14500	15000

Printed on 25/04/2024 22:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..