

EARTHMAX SR 51 - Spécifications techniques



Description

EARTHMAX SR 51 (L-5) est un pneu radial **All Steel** (Tout Acier) particulièrement conçu pour les chargeuses et bulldozers. EARTHMAX SR 51 est idéal pour les opérations pénibles qui exigent une plus grande résistance aux coupures, une protection des flancs et une traction exceptionnelle.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Bulldozer • Chargeur

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	23.5 R 25
LI/SS	195 A2

Dimensions US Standard

Usa code	94046256
Overall Width (inch)	24.1
Overall Diameter (inch)	65.4
Static Loaded Radius (inch)	29.3
Rolling Circumference (inch)	192.2
Rim Rec	19.50/2.5
Star Rating	*
TRA Code	L5

Load capacity (lbs)

mph / psi	58	62	65	69	73
5	22700	23400	24700	25400	26800

Printed on 04/03/2024 16:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..