

EARTHMAX SR 53 - Spécifications techniques



Description

EARTHMAX SR 53 est un pneu radial All Steel (Tout Acier) particulièrement conçu pour les chargeuses, les bulldozers et les tombereaux surbaissés (LPDT) qui opèrent dans des conditions difficiles dans des milieux rocheux y compris les opérations dans les mines souterraines et les chantiers de démolition. La bande de roulement profonde L-5 et le mélange particulièrement résistant aux coupures réduit considérablement l'usure et confère une traction et stabilité exceptionnelles.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Bulldozer • Chargeur • Tombereau surbaissé

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	17.5 R 25
LI/SS	176 A2

Dimensions US Standard

Usa code	94045808
Overall Width (inch)	17.1
Overall Diameter (inch)	55.1
Static Loaded Radius (inch)	25.1
Rolling Circumference (inch)	165.9
Rim Rec	14.00/1.5
Star Rating	*
TRA Code	L5

Load capacity (lbs)

mph / psi	58	62	65	69	73
5	13200	13600	14300	14800	15700

Printed on 26/04/2024 09:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..