

EARTHMAX SR 53 - Spécifications techniques



Description

EARTHMAX SR 53 est un pneu radial All Steel (Tout Acier) particulièrement conçu pour les chargeuses, les bulldozers et les tombereaux surbaissés (LPDT) qui opèrent dans des conditions difficiles dans des milieux rocheux y compris les opérations dans les mines souterraines et les chantiers de démolition. La bande de roulement profonde L-5 et le mélange particulièrement résistant aux coupures réduit considérablement l'usure et confère une traction et stabilité exceptionnelles.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Bulldozer • Chargeur • Tombereau surbaissé

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	35/65 R 33
LI/SS	224 A2

Dimensions US Standard

Usa code	94055036
Overall Width (inch)	35.8
Overall Diameter (inch)	81.2
Static Loaded Radius (inch)	36
Rolling Circumference (inch)	244.7
Rim Rec	28.00/3.5
Rim Alt	-
Star Rating	**
TRA Code	L5

Load capacity (lbs)

mph / psi	76	80	83	87	91	94
5	52000	55100	56800	58400	60000	61500

Printed on 26/04/2024 09:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..