

EARTHMAX SR 55 - Spécifications techniques



Description

EARTHMAX SR 55 (L-55) est un pneu radial All Steel (Tout Acier) spécialement conçu pour les chargeuses, les bulldozers et les chargeurs-transporteurs qui opèrent dans les conditions les plus pénibles, comme les carrières et les mines et les chantiers de démolition. Grâce au dessin de la bande de roulement extra profonde et lisse, EARTHMAX SR 55 est capable d'atteindre des niveaux de productivité élevés, avec des temps d'arrêt machine inférieurs. Les opérateurs des machines en apprécieront aussi stabilité et traction excellentes.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Bulldozer • Chargeur-transporteur LHD • Chargeur

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	17.5 R 25
LI/SS	182 A2

Dimensions International Standard

Overall Width (mm)	453
Overall Diameter (mm)	1399
Static Loaded Radius (mm)	630
Rolling Circumference (mm)	4211
Rim Rec	14.00/1.5
Star Rating	**
TRA Code	L5S

Load capacity (Kg)

km/h / bar	5.25	5.50	5.75	6.00	6.25	6.50
10	7300	7500	7750	8000	8250	8500

Printed on 25/04/2024 06:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..