

# EARTHMAX SR LOADER - Spécifications techniques



## Description

EARTHMAX SR LOADER est un pneu OTR particulièrement conçu pour les opérations de chargement et nivellement, ainsi que pour les applications de transport avec tombereaux articulés. Sa carcasse All Steel (Tout Acier) renforcée par des ceintures en acier multicouche et le composé exclusif de la bande de roulement offrent une résistance exceptionnelle aux déchirures et crevaisons, ce qui se traduit par une durée de vie plus longue du pneu. EARTHMAX SR LOADER est doté d'un dessin exclusif de la bande de roulement qui assure d'excellentes propriétés d'auto-nettoyage et une traction optimale sur une large gamme de terrains.

## UM

US Standard

## Construction

 RADIAL

## Machinery

OTR: Tombereau articulé • Bulldozer • Chargeur

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	26.5 R 25
LI/SS	193 B/202 A2

## Dimensions US Standard

Usa code	94064847
TMPH	158
Overall Width (inch)	26.8
Overall Diameter (inch)	68.3
Static Loaded Radius (inch)	30
Rolling Circumference (inch)	203.9
Rim Rec	22.00/3.0
Star Rating	**/*
TRA Code	E3/L3

## Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	20900	21500	22700	23400	24700	25400
5	28300	29100	30900	32000	33100	-

Printed on 25/04/2024 23:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..