

EARTHMAX SR LOADER - Spécifications techniques



Description

EARTHMAX SR LOADER est un pneu OTR particulièrement conçu pour les opérations de chargement et nivellement, ainsi que pour les applications de transport avec tombereaux articulés. Sa carcasse All Steel (Tout Acier) renforcée par des ceintures en acier multicouche et le composé exclusif de la bande de roulement offrent une résistance exceptionnelle aux déchirures et crevaisons, ce qui se traduit par une durée de vie plus longue du pneu. EARTHMAX SR LOADER est doté d'un dessin exclusif de la bande de roulement qui assure d'excellentes propriétés d'auto-nettoyage et une traction optimale sur une large gamme de terrains.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Tombereau articulé • Bulldozer • Chargeur

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	29.5 R 25
LI/SS	200 B/208 A2

Dimensions US Standard

Usa code	94065608
TMPH	185
Overall Width (inch)	30.2
Overall Diameter (inch)	73.2
Static Loaded Radius (inch)	32.2
Rolling Circumference (inch)	218.5
Rim Rec	25.00/3.5
Star Rating	**/*
TRA Code	E3/L3

Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	25400	26000	27600	28300	30000	30900
5	34200	35300	37500	38600	39700	-

Printed on 25/04/2024 21:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..