

EM 933 SUPER - Spécifications techniques



Description

L'EM 933 SUPER a été spécialement conçu pour les pelles utilisées pour les creusements et pour les opérations de chargement. La conception exceptionnelle de ses flancs, avec une nervure de bordure proéminente, assure un contact étroit entre les deux pneus, évitant ainsi d'utiliser un anneau en caoutchouc spécial pour empêcher les pierres de pénétrer. La conception unique de la bande de roulement offre une traction supérieure dans des conditions d'applications à charges lourdes. L'EM 933 SUPER offre également un confort de conduite exceptionnel et des propriétés d'auto-nettoyage améliorées.

UM

US Standard

Construction

 BIAS

Machinery

Industriel: Pelleteuse

Version	STANDARD
Type	TT
Tyre Size	290/90 - 20
LI/SS	152 B / 168 A2

Dimensions US Standard

Usa code	94070183
Ply Rating	18
Overall Width (inch)	11.6
Overall Diameter (inch)	41.5
Rim Rec	8.00
TRA Code	E2

Load capacity (lbs)

mph / psi	131
5	12350
30	7780

Printed on 27/04/2024 07:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..