

EM 933 SUPER - Fiche de données



Description

L'EM 933 SUPER a été spécialement conçu pour les pelles utilisées pour les creusements et pour les opérations de chargement. La conception exceptionnelle de ses flancs, avec une nervure de bordure proéminente, assure un contact étroit entre les deux pneus, évitant ainsi d'utiliser un anneau en caoutchouc spécial pour empêcher les pierres de pénétrer. La conception unique de la bande de roulement offre une traction supérieure dans des conditions d'applications à charges lourdes. L'EM 933 SUPER offre également un confort de conduite exceptionnel et des propriétés d'auto-nettoyage améliorées.

UM

US Standard

Construction

 BIAS

Machinery

Industriel: Pelleteuse

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	OW	OD	Type
290/90 - 20	STANDARD	94070183	E2	152 B / 168 A2	18	8.00		11.6	41.5	TT

Printed on 27/04/2024 06:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..