

# EM 936 LOADER SPECIAL - Spécifications techniques



## Description

EM 936 LOADER SPECIAL a été spécialement conçu pour les chargeurs télescopiques dans les applications de chargement. Il assure un grand confort pour la manutention, et il fournit une excellente traction même dans des conditions de service pénibles.

## UM

US Standard

## Construction

 BIAS

## Machinery

Industriel: Chargeur • Chargeuse télescopique

|           |                               |
|-----------|-------------------------------|
| Version   | STANDARD                      |
| Type      | TL                            |
| Tyre Size | 16.0/70 - 20<br>(405/70 - 20) |
| LI/SS     | 149 B                         |

## Dimensions US Standard

|                              |          |
|------------------------------|----------|
| Usa code                     | 94028771 |
| Ply Rating                   | 14       |
| Overall Width (inch)         | 15.9     |
| Overall Diameter (inch)      | 42.9     |
| Static Loaded Radius (inch)  | 18.9     |
| Rolling Circumference (inch) | 129.7    |
| Rim Rec                      | 13 SDC   |
| Rim Alt                      | 13       |
| TRA Code                     | E2       |

## Load capacity (lbs)

|           |      |
|-----------|------|
| mph / psi | 51   |
| 30        | 7150 |

Printed on 25/04/2024 22:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..