

EM 936 SUPER - Fiche de données



Description

EM 936 SUPER a été particulièrement conçu pour les excavatrices et chargeurs télescopiques dans les opérations d'excavation et chargement ainsi que dans les applications de transport. Grâce à la largeur de la bande de roulement augmentée de 8-10%, EM 936 SUPER se distingue de par une stabilité exceptionnelle et par son extraordinaire confort de conduite. Le pneu assure aussi un grand confort pour la manutention, et il fournit une excellente traction même dans des conditions de service pénibles.

UM

US Standard

Construction

❖ BIAS

Machinery

Industriel: Pelleteuse

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
10.00 - 20	STANDARD	94061860	E2	145 B	14	7.5	7.0 ; 8.0	10.9	42.5	19.7	131.3	TT
10.00 - 20	STANDARD	94062690	E2	146 B	16	7.5	7.0 ; 8.0	10.9	42.5	19.7	131.3	TT

Printed on 26/04/2024 08:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..