

EM 939 - Spécifications techniques



Description

EM 939 a été particulièrement conçu pour les excavateurs dans les applications de la construction de la route. Il offre une bande de roulement plus profonde avec plus pavés pour assurer un cycle de vie plus long au pneu. Le dessin spécial des pavés garantit tant une excellente traction latérale que des propriétés élevées d'auto-nettoyage. Le dessin unique de la bande de roulement garantit une excellente résistance aux déchirures et crevaisons tandis que la carcasse robuste assure un cycle de vie plus long.

UM

International Standard

Construction

 BIAS

Machinery

Industriel: Pelleteuse

Version	STANDARD
Type	TT
Tyre Size	10.00 - 20

Dimensions International Standard

Ply Rating	18
Section Width (mm)	280
Overall Diameter (mm)	1075
Rim Rec	7.5
Rim Alt	7.0 ; 8.0

Load capacity (Kg)

km/h / bar	8.50
50	3250

Printed on 03/05/2024 15:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..