

FARM 2000 - Spécifications techniques



Description

Le pneu FARM 2000 est adapté pour les tracteurs dans les applications de travail de la terre. Ce pneu a été conçu avec un mélange résistant aux coupures et déchirures, pour assurer une durabilité supérieure. Grâce à la carcasse particulièrement robuste, FARM 2000 garantit une capacité de charge élevée. Il assure aussi une excellente traction et des grandes propriétés d'auto-nettoyage.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Tracteur

Version	STANDARD
Type	TL
Tyre Size	260/70 - 15.3
LI/SS DRIVE WHEEL	114 A8
LI/SS FREE ROLLING	126 A8

Dimensions International Standard

Section Width (mm)	265
Overall Diameter (mm)	775
Static Loaded Radius (mm)	349
Rolling Circumference (mm)	2294
SRI (mm)	360
Rim Rec	9.00
ECE	E11-106R-003516

Load capacity (Kg)

	km/h / bar	3.60
	10 FR	2380
	25 FR	2025
	30 FR	1905
	40 FR	1700
	10 DW	1650
	25 DW	1405
	30 DW	1320
	40 DW	1180

Printed on 24/04/2024 22:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..