

FARM HIGHWAY TOUGH - Spécifications techniques



Description

FARM HIGHWAY TOUGH est un pneu à haute vitesse conçu pour les applications de transport et le labour du sol avec remorques et outils agricoles. Il offre une capacité de charge élevée même à grande vitesse et il assure une longue durée de vie du pneu.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Outillage agricole • Remorque

Version	STANDARD
Type	TL
Tyre Size	11L - 15 FI
LI/SS	128 J

Dimensions International Standard

Ply Rating	12
Section Width (mm)	279
Overall Diameter (mm)	777
Static Loaded Radius (mm)	347
Rolling Circumference (mm)	2214
Rim Rec	8 LB
Rim Alt	10 LB ; 8 J
ECE	E11-54R-0017871

Load capacity (Kg)

km/h / bar	6.20
100	1800

Printed on 23/04/2024 21:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..