

# FARM HIGHWAY TOUGH - Spécifications techniques



## Description

FARM HIGHWAY TOUGH est un pneu à haute vitesse conçu pour les applications de transport et le labour du sol avec remorques et outils agricoles. Il offre une capacité de charge élevée même à grande vitesse et il assure une longue durée de vie du pneu.

## UM

US Standard

## Construction

 BIAS

## Machinery

Agriculture: Outillage agricole • Remorque

Version	STANDARD
Type	TL
Tyre Size	9.5L - 15 FI

## Dimensions US Standard

Usa code	94039920
Ply Rating	8
Section Width (inch)	9.6
Overall Diameter (inch)	30.2
Static Loaded Radius (inch)	13.5
Rolling Circumference (inch)	85.9
Rim Rec	7.00
Rim Alt	8 LB

## Load capacity (lbs)

mph / psi	60
62	2680

Printed on 23/04/2024 20:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..