

FARM HIGHWAY TOUGH - Fiche de données



Description

FARM HIGHWAY TOUGH est un pneu à haute vitesse conçu pour les applications de transport et le labour du sol avec remorques et outils agricoles. Il offre une capacité de charge élevée même à grande vitesse et il assure une longue durée de vie du pneu.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Outillage agricole • Remorque

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
10.00 - 15 FI	STANDARD	94044733	128 J	8	8 LB		10.8	33.6	0	0	TL	E11-54R-0017870
11L - 15 FI	STANDARD	94032518	128 J	12	8 LB	10 LB ; 8 J	11	30.6	13.7	87.2	TL	E11-54R-0017871
11L - 15 FI	STANDARD	94039937	120 J	8	8 LB	10 LB ; 8 J	11	30.6	13.7	87.2	TL	E11-54R-0018902
12.5L - 15 FI	STANDARD	94032525	134 J	12	10 LB		12.5	32.1	14.3	91.5	TL	E11-54R-0019049
9.5L - 15 FI	STANDARD	94037605		12	7.00	8 LB	9.6	30.2	13.5	85.9	TL	
9.5L - 15 FI	STANDARD	94039920		8	7.00	8 LB	9.6	30.2	13.5	85.9	TL	

Printed on 23/04/2024 21:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..