

FARM SPECIAL - Spécifications techniques



Description

FARM SPECIAL est un pneu pour tracteurs approprié pour les opérations de travail de la terre. La carcasse robuste garantit un haut niveau de résistance aux crevaisons et un cycle de vie plus long, tandis que les épaules arrondies évitent d'endommager le sol et protègent donc les précieuses cultures. FARM SPECIAL se distingue de par le dessin unique de sa bande de roulement avec des éléments mud breaker (briseurs de boue) qui optimisent les propriétés d'auto nettoyage. De plus, l'angle à double orientation des revés assure une excellente traction avec un moindre glissement.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Tracteur

Version	STANDARD
Type	TT
Tyre Size	14.9 - 28
LI/SS	130 A6

Dimensions International Standard

Ply Rating	8
Section Width (mm)	375
Overall Diameter (mm)	1355
Static Loaded Radius (mm)	620
Rolling Circumference (mm)	4105
SRI (mm)	650
Rim Rec	W 13
Rim Alt	W 11 ; W 12
ECE	E11-106R-005535
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.80
30	1900

Printed on 26/04/2024 18:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..