

FL 252 - Spécifications techniques



Description

FL 252 est un pneu adapté pour les applications de récolte du foin avec andaineurs rotatifs/faneuses ainsi que pour les opérations logistiques avec chariots élévateurs. Ce pneu garantit une excellente durabilité, tandis que le dessin spécial de la bande de roulement assure un maximum de stabilité pendant les opérations de levage.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Adaineur rotatif
Industriel: Chariot élévateur

Version	STANDARD
Type	TT
Tyre Size	8.25 - 15

Dimensions US Standard

Usa code	94006939
Ply Rating	14
Section Width (inch)	9.4
Overall Diameter (inch)	33.7
Rim Rec	6.50
Rim Alt	7.0

Load capacity (lbs)

mph / psi	116
15 LOAD WHEEL	9315
15 STEER WHEEL	7165
5 OTHER VEHICLES	9315
15 OTHER VEHICLES	7165
STATIC SIDE LOADER	10825

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 13/05/2025 16:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..