

FL 633 PERFORMA - Spécifications techniques



Description

Le nouveau pneu radial FL 633 PERFORMA conjugue les exigences de plusieurs applications en agriculture avec la demande croissante des services logistiques en agriculture. Particulièrement conçu pour les camions utilisés dans d'agriculture, FL 633 PERFORMA est une solution novatrice qui améliore les performances de tracteurs et camions afin de répondre aux exigences spécifiques de l'agriculture moderne. Grâce à sa carcasse extra-robuste, à sa capacité de charge exceptionnelle et à sa durabilité, FL 633 PERFORMA représente le prochain niveau des pneus Flotation, parfaits pour les multiples activités des champs et même pour rouler sur autoroute, jusqu'à 100 km/h.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Camions agricole

Version	STANDARD
Type	TL
Tyre Size	600/50 R 22.5
LI/SS	164 J

Dimensions International Standard

Overall Width (mm)	590
Overall Diameter (mm)	1170
Static Loaded Radius (mm)	534
Rolling Circumference (mm)	3559
Rim Rec	AG 20.00
ECE	E11-54R-0017858

Load capacity (Kg)

km/h / bar	6.50
100	5000

Printed on 22/04/2024 23:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..