

## FL 633 PERFORMA - Spécifications techniques



### Description

Le nouveau pneu radial FL 633 PERFORMA conjugue les exigences de plusieurs applications en agriculture avec la demande croissante des services logistiques en agriculture. Particulièrement conçu pour les camions utilisés dans d'agriculture, FL 633 PERFORMA est une solution novatrice qui améliore les performances de tracteurs et camions afin de répondre aux exigences spécifiques de l'agriculture moderne. Grâce à sa carcasse extra-robuste, à sa capacité de charge exceptionnelle et à sa durabilité, FL 633 PERFORMA représente le prochain niveau des pneus Flotation, parfaits pour les multiples activités des champs et même pour rouler sur autoroute, jusqu'à 100 km/h.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Camions agricole

Version	STANDARD
Type	TL
Tyre Size	600/50 R 22.5
LI/SS	164 J

## Dimensions US Standard

Usa code	94063581
Overall Width (inch)	23.2
Overall Diameter (inch)	46.1
Static Loaded Radius (inch)	21
Rolling Circumference (inch)	140.1
Rim Rec	AG 20.00
ECE	E11-54R-0017858

## Load capacity (lbs)

mph / psi	94
62	11000

Printed on 23/04/2024 00:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..