

## FL 635 - Fiche de données



### Description

FL 635 est un pneu radial Flotation adapté pour une utilisation tant sur route que dans les champs. Le dessin particulier à blocs de la bande de roulement a été conçu pour des applications de presses à balles de foin. Grâce à l’empreinte qui fournit une excellente répartition de la pression sur le terrain, le pneu FL 635 réduit nettement le compactage du sol, préservant ainsi la valeur des cultures. Le pneu assure des qualités d’autonettoyage excellentes, d’excellentes durabilité et traction ainsi que des grandes propriétés de vitesse.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Presse à paille

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
<b>620/40 R 22.5</b>	STANDARD	94048038	154 D	AG 20.00		24.6	42	18.5	127.9	TL	E4-106R-002399
<b>650/55 R 22.5</b>	STANDARD	94043521	167 D	AG 20.00		25.4	50.7	22.4	153.6	TL	E4-106R-000803
<b>710/40 R 22.5</b>	STANDARD	94053285	161 D	AG 24.00		28.6	44.9	20.1	136.5	TL	E11-106R-003014
<b>750/45 R 22.5</b>	STANDARD	94048786	168 D	AG 24.00		29.7	49.1	21.9	150	TL	E4-106R-002653

Printed on 22/02/2024 18:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..