

## FL 637 - Spécifications techniques



### Description

FL 637 est un pneu radial Flotation adapté pour les épandeurs, remorques et camions-citernes. La structure avec ceinture en acier garantit une durabilité supérieure et une plus grande capacité de charge. En plus de ses excellentes propriétés de flottaison qui se traduisent par un compactage réduit du sol, ce pneu montre des extraordinaires propriétés d'autonettoyage. Le dessin directionnel de la bande de roulement assure une traction exceptionnelle aussi à des vitesses jusqu'à 70 km/h.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Épandeur • Véhicule citerne • Remorque

Version	STANDARD
Type	TL
Tyre Size	520/50 R 17
LI/SS	151D/148E

## Dimensions US Standard

Usa code	94054909
Section Width (inch)	20.3
Overall Diameter (inch)	37.5
Static Loaded Radius (inch)	16.3
Rolling Circumference (inch)	115.4
Rim Rec	16.00
ECE	E11-106R-004070

## Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	73
45	2020	2580	3130	3550	4100	4660	5150	5630	6180	6940
40	2220	2820	3430	3880	4500	5100	5630	6160	6780	7610
30	2680	3410	4140	4700	5430	6170	6810	7460	8200	9200
25	3010	3840	4660	5280	6120	6940	7660	8390	9210	10350
20	3340	4250	5170	5860	6780	7700	8510	9310	10230	11490
15	3490	4450	5410	6140	7100	8060	8910	9740	10700	12030
5	3980	5070	6160	6990	8080	9180	10140	11100	12190	13690

Printed on 19/04/2024 22:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..