

FL 639 - Spécifications techniques



Description

FL 639 est un pneu radial Flotation et de transport pour une utilisation essentiellement aux champs qui convient tout particulièrement pour les applications avec épandeurs. L'empreinte large garantit un moindre compactage du sol, ce qui permet une plus grande productivité des cultures. La bande de roulement renforcée et la protection du flanc contribuent à en allonger le cycle de vie. FL 639 assure une traction excellente même que des propriétés exceptionnelles d'autonettoyage.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Épandeur

Version	STANDARD
Type	TL
Tyre Size	850/40 R 26.5
LI/SS	173 D / 184 A8

Dimensions US Standard

Usa code	94064779
Section Width (inch)	33.9
Overall Diameter (inch)	53.3
Static Loaded Radius (inch)	23.6
Rolling Circumference (inch)	162.3
Rim Rec	AG 28.00
ECE	E11-106R-006228

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58
45	4180	5360	6660	7570	8740	9920	10820	11870	13040
40	4590	5870	7310	8310	9600	10890	11890	13040	14330
30	5560	7110	8850	10060	11620	13180	14400	15780	17340
25	6350	8130	10120	11510	13290	15080	16470	18050	19840
20	6930	8870	11040	12550	14510	16450	17970	19700	21640
15	7250	9290	11550	13140	15180	17220	18790	20610	22640
5	8260	10580	13160	14970	17280	19610	21420	23480	25790

Printed on 19/04/2024 21:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..