

FLOTATION 351 - Spécifications techniques

Description

FLOTATION 351 est un pneu diagonal Flotation idéal pour les applications de transport avec les remorques. Les crampons extra profonds fournissent une traction exceptionnelle et allongent la vie du pneu. FLOTATION 351 est le pneu idéal sur les surfaces mouillées et humides en assurant une capacité de charge élevée.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Remorque



Version	STANDARD
Type	TL
Tyre Size	48 X 25.00 - 20
LI/SS	144 B

Dimensions US Standard

Usa code	94025657
Ply Rating	10
Section Width (inch)	24.8
Overall Diameter (inch)	50
Static Loaded Radius (inch)	22
Rolling Circumference (inch)	149
Rim Rec	20.50 HF
Rim Alt	20.50 VF
TRA Code	HF3

Load capacity (lbs)

mph / psi	35
30	6150

Printed on 27/02/2024 05:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..