

FLOTATION 558 - Spécifications techniques



Description

FLOTATION 558 est un pneu Flotation à couches croisées adapté pour les moissonneuses et les presses à balles de foin et les remorques tant sur route que hors route. Il est particulièrement recommandé pour toutes les opérations du travail des sols qui nécessitent une excellente traction et une capacité de charge élevée.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Presse à paille • Moissonneuse • Véhicule citerne • Remorque

| | |
|--------------------|------------------|
| Version | ARAMID BELTED HD |
| Type | TL |
| Tyre Size | 500/45 - 22.5 |
| LI/SS DRIVE WHEEL | 142 A8/138 B |
| LI/SS FREE ROLLING | 154 A8/150 B |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Ply Rating | 16 |
| Section Width (mm) | 500 |
| Overall Diameter (mm) | 1045 |
| Static Loaded Radius (mm) | 471 |
| Rolling Circumference (mm) | 3167 |
| Rim Rec | AG 16.00 |
| ECE | E11-106R-005352 |

Load capacity (Kg)

| km/h / bar | 3.20 | 3.40 | 3.60 |
|------------|------|------|------|
| 10 FR | 4900 | 5075 | 5250 |
| 20 FR | 4410 | 4570 | 4725 |
| 30 FR | 3920 | 4060 | 4200 |
| 40 FR | 3500 | 3625 | 3750 |
| 50 FR | 3150 | 3265 | 3350 |
| 10 DW | 3465 | 3590 | 3710 |
| 20 DW | 3120 | 3230 | 3340 |
| 30 DW | 2770 | 2875 | 2970 |
| 40 DW | 2475 | 2565 | 2650 |
| 50 DW | 2230 | 2310 | 2360 |

Printed on 25/04/2024 21:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..