

FLOTATION 648 - Spécifications techniques



Description

FLOTATION 648 est particulièrement adapté pour les transports aux champs et sur la route et pour les applications avec épandeurs. Certaines tailles conviennent pour les moissonneuses/presses à balles de foin. Le dessin particulier de la bande de roulement permet le transport de charges très lourdes à de basses pressions, ce qui garantit un moindre compactage du sol tout en protégeant les cultures des dommages.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Presse à paille • Moissonneuse • Épandeur

Version	STANDARD
Type	TL
Tyre Size	500/50 - 17
LI/SS DRIVE WHEEL	128 A8/124 B
LI/SS FREE ROLLING	140 A8/136 B

Dimensions International Standard

Ply Rating	10
Section Width (mm)	510
Overall Diameter (mm)	945
Static Loaded Radius (mm)	416
Rolling Circumference (mm)	2750
Rim Rec	16.00
ECE	E4-106R-002713

Load capacity (Kg)

km/h / bar	1.50	1.70	2.00
10 FR	2960	3185	3500
20 FR	2665	2865	3150
30 FR	2370	2550	2800
40 FR	2115	2275	2500
50 FR	1905	2050	2240
10 DW	2130	2290	2520
20 DW	1915	2060	2270
30 DW	1700	1830	2015
40 DW	1520	1635	1800
50 DW	1370	1470	1600

Printed on 23/04/2024 17:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..