

## FLOTATION 648 - Spécifications techniques



### Description

FLOTATION 648 est particulièrement adapté pour les transports aux champs et sur la route et pour les applications avec épandeurs. Certaines tailles conviennent pour les moissonneuses/presses à balles de foin. Le dessin particulier de la bande de roulement permet le transport de charges très lourdes à de basses pressions, ce qui garantit un moindre compactage du sol tout en protégeant les cultures des dommages.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Presse à paille • Moissonneuse • Épandeur

Version	STANDARD
Type	TL
Tyre Size	500/50 - 17
LI/SS DRIVE WHEEL	145 A8/141 B
LI/SS FREE ROLLING	157 A8/154 B

## Dimensions International Standard

Ply Rating	18
Section Width (mm)	510
Overall Diameter (mm)	945
Static Loaded Radius (mm)	416
Rolling Circumference (mm)	2750
Rim Rec	AG 16.00
ECE	E4-106R-002305

## Load capacity (Kg)

km/h / bar	3.80	3.90	4.00
10 FR	5605	5690	5775
20 FR	5045	5120	5200
30 FR	4485	4555	4620
40 FR	4005	4065	4125
50 FR	3605	3660	3750
10 DW	3940	3995	4060
20 DW	3545	3595	3655
30 DW	3155	3200	3250
40 DW	2815	2855	2900
50 DW	2535	2570	2575

Printed on 29/11/2023 16:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..