

## FLOTATION 648 - Spécifications techniques



### Description

FLOTATION 648 est particulièrement adapté pour les transports aux champs et sur la route et pour les applications avec épandeurs. Certaines tailles conviennent pour les moissonneuses/presses à balles de foin. Le dessin particulier de la bande de roulement permet le transport de charges très lourdes à de basses pressions, ce qui garantit un moindre compactage du sol tout en protégeant les cultures des dommages.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Presse à paille • Moissonneuse • Épandeur

Version	STANDARD
Type	TL
Tyre Size	500/60 - 22.5
LI/SS DRIVE WHEEL	145 A8/142 B
LI/SS FREE ROLLING	157 A8/154 B

## Dimensions International Standard

<b>Ply Rating</b>	12
<b>Section Width (mm)</b>	500
<b>Overall Diameter (mm)</b>	1170
<b>Static Loaded Radius (mm)</b>	510
<b>Rolling Circumference (mm)</b>	3489
<b>Rim Rec</b>	AG 16.00
<b>Rim Alt</b>	15.00 ; 17.00
<b>ECE</b>	E11-106R-004552

## Load capacity (Kg)

km/h / bar	1.50	2.00	2.40
<b>10 FR</b>	4390	5195	5775
<b>20 FR</b>	3950	4675	5200
<b>30 FR</b>	3510	4155	4620
<b>40 FR</b>	3135	3710	4125
<b>50 FR</b>	2820	3340	3750
<b>10 DW</b>	3085	3645	4060
<b>20 DW</b>	2780	3280	3655
<b>30 DW</b>	2470	2920	3250
<b>40 DW</b>	2205	2605	2900
<b>50 DW</b>	1985	2345	2650

Printed on 23/04/2024 17:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..