

FLOTATION 648 - Spécifications techniques



Description

FLOTATION 648 est particulièrement adapté pour les transports aux champs et sur la route et pour les applications avec épandeurs. Certaines tailles conviennent pour les moissonneuses/presses à balles de foin. Le dessin particulier de la bande de roulement permet le transport de charges très lourdes à de basses pressions, ce qui garantit un moindre compactage du sol tout en protégeant les cultures des dommages.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Presse à paille • Moissonneuse • Épandeur

Version	STANDARD
Type	TL
Tyre Size	500/60 - 22.5
LI/SS DRIVE WHEEL	145 A8/142 B
LI/SS FREE ROLLING	157 A8/154 B

Dimensions US Standard

Usa code	94006342
Ply Rating	12
Section Width (inch)	19.7
Overall Diameter (inch)	46.1
Static Loaded Radius (inch)	20.1
Rolling Circumference (inch)	137.4
Rim Rec	AG 16.00
Rim Alt	15.00 ; 17.00
ECE	E11-106R-004552

Load capacity (lbs)

mph / psi	22	29	35
5 FR	9680	11450	12730
10 FR	8710	10310	11460
20 FR	7740	9160	10180
25 FR	6910	8180	9090
30 FR	6220	7360	8270
5 DW	6800	8040	8950
10 DW	6130	7230	8060
20 DW	5450	6440	7160
25 DW	4860	5740	6390
30 DW	4380	5170	5840

Printed on 23/04/2024 18:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..