

FLOTATION 648 - Spécifications techniques



Description

FLOTATION 648 est particulièrement adapté pour les transports aux champs et sur la route et pour les applications avec épandeurs. Certaines tailles conviennent pour les moissonneuses/presses à balles de foin. Le dessin particulier de la bande de roulement permet le transport de charges très lourdes à de basses pressions, ce qui garantit un moindre compactage du sol tout en protégeant les cultures des dommages.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Presse à paille • Moissonneuse • Épandeur

Version	DUAL BEAD
Type	TL
Tyre Size	550/60 - 22.5
LI/SS DRIVE WHEEL	158 A8/154 B
LI/SS FREE ROLLING	171 A8/167 B

Dimensions International Standard

Ply Rating	20
Section Width (mm)	550
Overall Diameter (mm)	1240
Static Loaded Radius (mm)	540
Rolling Circumference (mm)	3725
Rim Rec	AG 16.00
ECE	E11-106R-004391

Load capacity (Kg)

km/h / bar	3.30	3.40	3.50
10 FR	8315	8465	8610
20 FR	7485	7615	7750
30 FR	6655	6770	6890
40 FR	5940	6045	6150
50 FR	5345	5440	5450
10 DW	5745	5850	5950
20 DW	5170	5265	5355
30 DW	4600	4680	4760
40 DW	4105	4180	4250
50 DW	3625	3685	3750

Printed on 23/04/2024 17:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..