

FLOTATION 648 - Spécifications techniques



Description

FLOTATION 648 est particulièrement adapté pour les transports aux champs et sur la route et pour les applications avec épandeurs. Certaines tailles conviennent pour les moissonneuses/presses à balles de foin. Le dessin particulier de la bande de roulement permet le transport de charges très lourdes à de basses pressions, ce qui garantit un moindre compactage du sol tout en protégeant les cultures des dommages.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Presse à paille • Moissonneuse • Épandeur

Version	STANDARD
Type	TL
Tyre Size	600/55 - 22.5
LI/SS DRIVE WHEEL	156 A8/153 B
LI/SS FREE ROLLING	169 A8/166 B

Dimensions US Standard

Usa code	94006427
Ply Rating	16
Section Width (inch)	23.6
Overall Diameter (inch)	48.4
Static Loaded Radius (inch)	21.3
Rolling Circumference (inch)	146.3
Rim Rec	AG 20.00
ECE	E4-106R-001564

Load capacity (lbs)

mph / psi	32	35	38
5 FR	16240	17080	17900
10 FR	14620	15380	16110
20 FR	12980	13670	14320
25 FR	11600	12200	12790
30 FR	10440	10980	11680
5 DW	11200	11770	12350
10 DW	10090	10590	11110
20 DW	8960	9420	9880
25 DW	8000	8410	8820
30 DW	7200	7570	8050

Printed on 08/12/2023 00:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..