

FLOTATION 648 - Spécifications techniques



Description

FLOTATION 648 est particulièrement adapté pour les transports aux champs et sur la route et pour les applications avec épandeurs. Certaines tailles conviennent pour les moissonneuses/presses à balles de foin. Le dessin particulier de la bande de roulement permet le transport de charges très lourdes à de basses pressions, ce qui garantit un moindre compactage du sol tout en protégeant les cultures des dommages.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Presse à paille • Moissonneuse • Épandeur

Version	STANDARD
Type	TL
Tyre Size	600/55 - 26.5
LI/SS DRIVE WHEEL	153 A8/149 B
LI/SS FREE ROLLING	165 A8/161 B

Dimensions International Standard

Ply Rating	12
Section Width (mm)	611
Overall Diameter (mm)	1354
Static Loaded Radius (mm)	581
Rolling Circumference (mm)	4017
Rim Rec	AG 20.00
ECE	E4-106R-002277

Load capacity (Kg)

km/h / bar	1.50	1.80	2.00
10 FR	6090	6775	7210
20 FR	5480	6100	6490
30 FR	4870	5420	5770
40 FR	4350	4840	5150
50 FR	3915	4355	4625
10 DW	4320	4800	5110
20 DW	3885	4320	4600
30 DW	3455	3840	4090
40 DW	3085	3430	3650
50 DW	2775	3085	3250

Printed on 23/04/2024 18:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..