

## FLOTATION 648 - Spécifications techniques



### Description

FLOTATION 648 est particulièrement adapté pour les transports aux champs et sur la route et pour les applications avec épandeurs. Certaines tailles conviennent pour les moissonneuses/presses à balles de foin. Le dessin particulier de la bande de roulement permet le transport de charges très lourdes à de basses pressions, ce qui garantit un moindre compactage du sol tout en protégeant les cultures des dommages.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Presse à paille • Moissonneuse • Épandeur

Version	STANDARD
Type	TL
Tyre Size	750/60 - 30.5
LI/SS DRIVE WHEEL	164 A8/160 B
LI/SS FREE ROLLING	176 A8/172 B

## Dimensions US Standard

Usa code	94006533
Ply Rating	12
Section Width (inch)	29.7
Overall Diameter (inch)	65.9
Static Loaded Radius (inch)	28
Rolling Circumference (inch)	194.3
Rim Rec	AG 24.00
ECE	E11-106R-003410

## Load capacity (lbs)

mph / psi	22	23	25
5 FR	20370	21150	21910
10 FR	18330	19040	19720
20 FR	16290	16930	17530
25 FR	14550	15110	15650
30 FR	13090	13600	13890
5 DW	14340	14890	15430
10 DW	12910	13400	13890
20 DW	11460	11920	12350
25 DW	10240	10640	11020
30 DW	9210	9580	9920

Printed on 29/11/2023 17:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..