

## FLOTATION 648 - Spécifications techniques



### Description

FLOTATION 648 est particulièrement adapté pour les transports aux champs et sur la route et pour les applications avec épandeurs. Certaines tailles conviennent pour les moissonneuses/presses à balles de foin. Le dessin particulier de la bande de roulement permet le transport de charges très lourdes à de basses pressions, ce qui garantit un moindre compactage du sol tout en protégeant les cultures des dommages.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Presse à paille • Moissonneuse • Épandeur

Version	HD
Type	TL
Tyre Size	850/50 - 30.5
LI/SS DRIVE WHEEL	176 A8/173 B
LI/SS FREE ROLLING	189 A8/185 B

## Dimensions International Standard

<b>Ply Rating</b>	18
<b>Section Width (mm)</b>	850
<b>Overall Diameter (mm)</b>	1650
<b>Static Loaded Radius (mm)</b>	710
<b>Rolling Circumference (mm)</b>	4935
<b>Rim Rec</b>	AG 28.00
<b>ECE</b>	E11-106R-004566

## Load capacity (Kg)

km/h / bar	2.30	2.40	2.50
10 FR	13735	14075	14420
20 FR	12360	12670	12980
30 FR	10985	11260	11535
40 FR	9810	10055	10300
50 FR	8830	9050	9250
10 DW	9465	9700	9940
20 DW	8520	8730	8945
30 DW	7570	7760	7950
40 DW	6760	6930	7100
50 DW	6085	6235	6500

Printed on 23/04/2024 18:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..