

FLOTATION TR 678 - Spécifications techniques



Description

FLOTATION TR 678 a été particulièrement conçu pour l'outillage agricole et les remorques tant sur route que hors route. Il permet de transporter des charges lourdes à de basses pressions, tout en assurant un moindre compactage du sol. Ce pneu garantit une traction exceptionnelle et possède d'excellentes qualités d'autonettoyage.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Outillage agricole • Remorque

| | |
|-----------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 650/45 - 22.5 |
| LI/SS | 160 D |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94005420 |
| Section Width (inch) | 25.6 |
| Overall Diameter (inch) | 45.3 |
| Static Loaded Radius (inch) | 19.8 |
| Rolling Circumference (inch) | 130 |
| Rim Rec | AG 20.00 |
| ECE | E11-106R-004399 |

Load capacity (lbs)

| | |
|-----------|-------|
| mph / psi | 58 |
| 40 | 10750 |

Printed on 19/04/2024 16:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..