

FLOTATION TR 678 - Fiche de données



Description

FLOTATION TR 678 a été particulièrement conçu pour l'outillage agricole et les remorques tant sur route que hors route. Il permet de transporter des charges lourdes à de basses pressions, tout en assurant un moindre compactage du sol. Ce pneu garantit une traction exceptionnelle et possède d'excellentes qualités d'autonettoyage.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Outillage agricole • Remorque

SIZE	Version	LI/SS	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
320/60 - 12	STANDARD		120 A8	132 A8		10.50 I		328	689	327	2111	TT	E11-106R-006617
280/60 - 15.5	STANDARD	128 A8				8.0		275	750	357	2250	TL	E11-106R-004262
280/60 - 15.5	STANDARD	115 A8				8.0		275	750	357	2250	TL	E11-106R-004261
500/45 - 20	STANDARD		148 A8	160 A8		16.00 DC		495	980			TL	E11-106R-006816
600/40 - 22.5	DUAL BEAD		157 A8	169 A8	20	AG 20.00		615	1085	483	3264	TL	E11-106R-006501
600/40 - 22.5	DUAL BEAD HD		157 A8	169 A8	20	AG 20.00		615	1085	483	3264	TL	E11-106R-004619
600/40 - 22.5	INDUSTRIAL		157 A8	169 A8	20	AG 20.00		615	1085	483	3264	TL	
650/45 - 22.5	STANDARD	166 B			20	AG 20.00		650	1150	502	3302	TL	E11-106R-004400
650/45 - 22.5	STANDARD	160 D				AG 20.00		650	1150	502	3302	TL	E11-106R-004399
650/45 - 22.5	STEEL BELTED	166 B			20	AG 20.00		650	1150	502	3302	TL	E11-106R-004401
710/40 - 22.5	ARAMID + STEEL BELTED	173 A8				AG 24.00		707	1165	0	0	TL	E11-106R-006011
710/40 - 22.5	STEEL BELTED	173 A8				AG 24.00		707	1165	545	3624	TL	E11-106R-006011

Printed on 23/02/2024 13:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..