

## FORESTECH - Spécifications techniques



### Description

FORESTECH est un pneu BKT avec ceintures d'acier, adapté pour les applications en forêt avec porteurs forestiers. Ce pneu offre une excellente traction même dans des conditions de service pénibles. La tringle robuste et la zone de l'épaule renforcée assurent une grande résistance aux perforations et une vie plus longue du pneu. Par conséquent, vous pourrez réaliser sans problèmes les opérations les plus exigeantes et difficiles dans la forêt.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Porteur

Version	STEEL BELTED
Type	TL
Tyre Size	750/55 - 26.5
LI/SS	177 A8/184 A2

## Dimensions US Standard

Usa code	94031719
Ply Rating	20
Section Width (inch)	29.7
Overall Diameter (inch)	58.5
Static Loaded Radius (inch)	26.8
Rolling Circumference (inch)	175.9
Rim Rec	AG 24.00
ECE	E11-106R-003347
TRA Code	LS2

## Load capacity (lbs)

mph / psi	73
25	16090
20	17220
5	19840

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 09/12/2024 10:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..