

FS 216 - Fiche de données



Description

FS 216 bénéficie d'un dessin robuste des crampons avec angles optimisés et plus larges pour améliorer les performances en thème de traction pour les porteurs forestiers et les débusqueuses. Ce pneu offre une excellente résistance aux coupures et déchirures même dans les conditions de service les plus critiques, assurant à tout moment un maximum de protection contre tous les éventuels dommages.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Débusqueuse

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
18.4 - 26	STEEL BELTED	LS2	10	DW 16 A		467	1476	682	4433	TT	E11-106R-003637
23.1 - 26	STEEL BELTED	LS2	10	DW 20 A ; DW 20 B		587	1615	726	4780	TT	E11-106R-003650
23.1 - 26	STEEL BELTED	LS2	14	DW 20 A ; DW 20 B		587	1615	726	4780	TT	E11-106R-003411
23.1 - 26	STEEL BELTED	LS2	16	DW 20 A ; DW 20 B		587	1615	726	4780	TL	E11-106R-003662
23.1 - 26	STEEL BELTED	LS2	20	DW 20 A ; DW 20 B		587	1615	726	4780	TT	E11-106R-004635
23.1 - 26	STEEL BELTED	LS2	12	DW 20 A ; DW 20 B		587	1615	726	4780	TT	E11-106R-003651
23.1 - 26	STEEL BELTED	LS2	16	DW 20 A ; DW 20 B		587	1615	726	4780	TT	E11-106R-003661
28L - 26	STEEL BELTED	LS2	20	DW 25 A ; DW 25 B		720	1660	742	4912	TL	E11-106R-006733
28L - 26	STEEL BELTED	LS2	26	DW 25 A ; DW 25 B		720	1660	742	4912	TL	E11-106R-006734
28L - 26	STEEL BELTED	LS2	14	DW 25 A ; DW 25 B		720	1660	742	4912	TL	E11-106R-003413
28L - 26	STEEL BELTED	LS2	18	DW 25 A ; DW 25 B		720	1660	742	4912	TL	E11-106R-003425
18.4 - 30	STEEL BELTED	LS2	10	DW 16 A		467	1577	724	4736	TT	E11-106R-003638
18.4 - 30	STEEL BELTED	LS2	14	DW 16 A		467	1577	724	4736	TT	E11-106R-004644
24. 5 - 32	STEEL BELTED	LS2	16	DH 21	DH 21 B	622	1831	836	5456	TL	E11-106R-003421
30.5L - 32	STEEL BELTED	LS2	26	DH 27	DH 27 B	775	1847	833	5466	TL	
30.5L - 32	STEEL BELTED	LS2	16	DH 27	DH 27 B	775	1847	833	5466	TL	E11-106R-003426
30.5L - 32	STEEL BELTED	LS2	20	DH 27	DH 27 B	775	1847	833	5466	TL	E11-106R-003439
30.5L - 32	STEEL BELTED	LS2	32	DH 27	DH 27 B	775	1847	833	5466	TL	
DH 35.5L - 32	STEEL BELTED	LS2	30	DH 31	DH 31 H	907	2011	912	5992	TL	E11-106R-006503
DH 35.5L - 32	STEEL BELTED	LS2	20	DH 31	DH 31 H	907	2011	912	5992	TL	E11-106R-003349
DH 35.5L - 32	STEEL BELTED	LS2	24	DH 31	DH 31 H	907	2011	912	5992	TL	
18.4 - 34	STEEL BELTED	LS2	10	DW 16 A		467	1679	768	5042	TT	E11-106R-004560
18.4 - 34	STEEL BELTED	LS2	14	DW 16 A		467	1679	768	5042	TL	E11-106R-003401

Printed on 26/04/2024 22:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..