

## GF 304 - Fiche de données



### Description

GF 304 est un pneu qui convient pour les applications avec les voitures de golf. GF 304 vous assure un maximum de confort ainsi qu'une excellente protection du terrain. GF 304 est aussi disponible en version "aramid belted", avec ceintures en aramide, pour donner une plus grande résistance aux perforations.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Voiturette de golf

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
18 X 8.50 - 8	ARAMID BELTED	94008056	4	7.00 I - 55 ; I - 70 ; I - 90		8.5	18.1	8	52.5	TL	E11-106R-005218
18 X 8.50 - 8	STANDARD	94008049	4	7.00 I - 55 ; I - 70 ; I - 90		8.5	18.1	8	52.5	TL	E11-106R-003442
18 X 8.50 - 8	STANDARD	94031078	6	7.00 I - 55 ; I - 70 ; I - 90		8.5	18.1	8	52.5	TL	E11-106R-005197

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 07/12/2024 21:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..