GIANT TRAX - Spécifications techniques

Description

GIANT TRAX a été conçu pour les chargeuses compactes qui opèrent sur les surfaces rugueuses que l'on trouve dans les parcs à ferraille et pour les applications de recyclage et minières. La bande de roulement extra profonde aux blocs plus larges et plus robustes assure d'excellentes qualités de traction, stabilité et résistance aux perforations. Le mélange spécial de la bande de roulement confère une extraordinaire résistance aux coupures et déchirures, ainsi qu'une excellente résistance à l'usure sur tout type de terrain.

UM

US Standard

Construction

BIAS

Machinery

Industriel: Chargeur compact

Version	STANDARD
Type	TL
Tyre Size	14 - 17.5

Dimensions US Standard

Usa code	94064403
Ply Rating	14
Section Width (inch)	13.8
Overall Diameter (inch)	36
Static Loaded Radius (inch)	16.6
Rolling Circumference (inch)	106.9
Rim Rec	10.50
ECE	E11-106R-006019

Load capacity (lbs)

mph / psi	80
5	8540
10	6750
15	6240

Printed on 19/04/2024 02:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..