

## GR 288 - Spécifications techniques



### Description

GR 288 (G-2/L-2) est un pneu polyvalent à carcasse diagonale pour niveleuses ou chargeuses. Ce pneu est idéal pour une utilisation dans le secteur bâtiment, préparation du site, construction routière ainsi que sur les autres sols mous ou boueux. Le dessin de la bande de roulement lui confère d'excellentes propriétés d'auto-nettoyage qui se traduisent par une excellente traction. Grâce à son mélange spécial résistant aux coupures et déchirures, ce pneu a une durée de vie élevée.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industriel: Bulldozer • Chargeur

OTR: Niveleuse

Version	STANDARD
Type	TL
Tyre Size	23.5 - 25

## Dimensions International Standard

Ply Rating	16
Overall Width (mm)	595
Overall Diameter (mm)	1610
Static Loaded Radius (mm)	708
Rolling Circumference (mm)	4782
Rim Rec	19.50/2.5
ECE	E11-106R-005406
TRA Code	G2/L2

## Load capacity (Kg)

km/h / bar	2.00	3.00
40	4750	-
10	-	9500

Printed on 27/04/2024 04:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..